

# Product datasheet

Specifications



## Easy UPS 3S 10 kVA 400 V 3:3 UPS for internal batteries

Local distributor code:  
422503538

E3SUPS10KHB

### Overview

<b>Presentation</b>	High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 10 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is for internal batteries, but is supplied without batteries, so you can easily customize the battery runtime. For battery runtime details, see the runtime charts published under the Documents tab.
<b>Lead Time</b>	Usually Ships within 6 Weeks

### Main

<b>Main Input Voltage</b>	400 V 3 phases
<b>Other Input Voltage</b>	380 V 415 V
<b>Main Output Voltage</b>	400 V 3 phases
<b>Other Output Voltage</b>	380 V 415 V
<b>Rated Power In W</b>	10 kW
<b>Rated Power In Va</b>	10 kVA
<b>Provided Equipment</b>	Dust filter Installation guide

### Batteries & Runtime

<b>Efficiency</b>	<a href="#">View Efficiency Graph</a>
<b>Battery Type</b>	VRLA
<b>Battery Voltage</b>	240 V
<b>Maximum Short-Circuit Current</b>	10 kA
<b>Number Of Battery Filled Slots</b>	0
<b>Number Of Battery Free Slots</b>	3
<b>Discharge Battery Voltage</b>	+/- 198 V DC

### Physical

<b>Colour</b>	White (RAL 9003)
<b>Height</b>	140 cm
<b>Width</b>	38 cm
<b>Depth</b>	92.8 cm
<b>Net Weight</b>	112 kg

Usb Compatible	Yes
----------------	-----

## Input

Maximum Input Current	18 A
Input Harmonic Distortion	Less than 3 % for full load
Load Power Factor	0.9 leading to 0.9 lagging
Input Power Factor At Full Load	0.99
Input Voltage Limits	304...477 V
Network Frequency	45...65 Hz

## Output

Maximum Configurable Power In Va	10 kVA
Maximum Configurable Power In W	10 kW
Output Frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic Distortion	Less than 3 %
Output Harmonic Distortion	< 3% linear load
Output Overload Operation	130-150% for 1 minute and 125-130% for 10 minutes
Output Voltage Tolerance	+/- 1.5 %
Ups Type	Double conversion online

## Conformance

Product Certifications	CE EAC RCM
------------------------	------------------

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3333 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0.00...15240.00 m
Acoustic Level	60 dBA
Heat Dissipation	516 W
Ip Degree Of Protection	IP20

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	164 cm
Package 1 Width	101.4 cm
Package 1 Length	56.3 cm

---

Package 1 Weight 145 kg

## Contractual warranty

---

Warranty 1 year on-site repair or replace with factory authorized Start-Up

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Transparency

---

### Reach Regulation

[REACH Declaration](#)

---

### Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

---

### China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

---

### Environmental Disclosure

[Product Environmental Profile](#)

---

### Circularity Profile

[End of Life Information](#)

---