

# Product datasheet

Specifications



## APC Easy UPS On-Line, 3kVA/2400W, Tower, 230V, 6x IEC C13 + 1x IEC C19 outlets, Intelligent Card Slot, LCD

SRV3KI

### Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead Time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Product Or Component Type</b>	Uninterruptible power supply (UPS)
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated Power In W</b>	2400 W
<b>Rated Power In Va</b>	3000 VA
<b>Input Connection Type</b>	IEC 60320 C20
<b>Output Connection Type</b>	6 IEC 60320 C13 1 IEC 60320 C19
<b>Cable Length</b>	1.5 m
<b>Number Of Cables</b>	1
<b>Provided Equipment</b>	1 IEC 60320 C19 to Schuko power cable 1 IEC 60320 C13 to C14 power cable 1 USB cable 1 RS-232 configuration cable user manual

### Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a>
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a>
<b>Battery Type</b>	Lead-acid battery
<b>Battery Voltage</b>	72 V
<b>Number Of Battery Filled Slots</b>	0
<b>Number Of Battery Free Slots</b>	0
<b>Battery Recharge Time</b>	4 h
<b>Battery Life</b>	3...5 year(s)
<b>Replacement Battery</b>	<a href="#">APCRBCV205</a>

---

Battery Charger Power	60 W rated
-----------------------	------------

## General

---

Number Of Power Module Filled Slots	0
-------------------------------------	---

---

Number Of Power Module Free Slots	0
-----------------------------------	---

---

Redundant	No
-----------	----

## Physical

---

Colour	Black (RAL 7010)
--------	------------------

---

Height	33.6 cm
--------	---------

---

Width	19 cm
-------	-------

---

Depth	42.5 cm
-------	---------

---

Net Weight	26.8 kg
------------	---------

---

Mounting Location	Front
-------------------	-------

---

Mounting Preference	No preference
---------------------	---------------

---

Mounting Mode	Not rack-mountable
---------------	--------------------

---

Usb Compatible	Yes
----------------	-----

---

Mounting Position	Vertical
-------------------	----------

## Input

---

Input Voltage Limits	110...285 V half load 160...280 V full load
----------------------	--

---

Network Frequency	40...70 Hz auto sensing
-------------------	-------------------------

## Output

---

Maximum Configurable Power In Va	3000 VA
----------------------------------	---------

---

Maximum Configurable Power In W	2400 W
---------------------------------	--------

---

Output Frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

---

Harmonic Distortion	3 %
---------------------	-----

---

Ups Type	Double conversion online
----------	--------------------------

---

Wave Type	Sine wave
-----------	-----------

---

Efficiency	88 % (full load)
------------	------------------

---

Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
------------------------	--

---

Bypass Type	Internal bypass (automatic and manual)
-------------	--

---

Crest Factor	3 : 1
--------------	-------

## Conformance

---

Product Certifications	CE UKCA EAC TISI
------------------------	---------------------------

---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	50 dBA
Heat Dissipation	910 Btu/h
Ip Degree Of Protection	IP20

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Free Slots	1
Control Panel	Multifunction LCD status and control console

## Surge Protection and Filtering

Surge Energy Rate	600 J
-------------------	-------

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	46.5 cm
Package 1 Width	32.5 cm
Package 1 Length	56.5 cm
Package 1 Weight	29 kg

## Logistical informations

Country Of Origin	CN
-------------------	----

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability


**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Energy Efficient Transparency RoHS/REACH

## Resource performance

 Energy Efficient Product

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)