

**TERMSERIES
ZQV 1.5N/R6.4/19 GE**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image

TERMSERIES accessories include:

- Spare relay
- Base
- Partition plates
- Cross-connections
- Power-feed modules

General ordering data

| | |
|------------|-----------------------------|
| Type | ZQV 1.5N/R6.4/19 GE |
| Order No. | 1193690000 |
| Version | TERMSERIES, Cross-connector |
| GTIN (EAN) | 4032248976645 |
| Qty. | 10 pc(s). |

Data sheet

**TERMSERIES
ZQV 1.5N/R6.4/19 GE**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Width | 119 mm | Width (inches) | 4.685 inch |
| Height | 13.1 mm | Height (inches) | 0.516 inch |
| Depth | 4.9 mm | Depth (inches) | 0.193 inch |
| Net weight | 4.647 g | | |

Temperatures

| | | | |
|-----------------------------|----------------|-----------------------------|----------------|
| Operating temperature, max. | 60 °C | Operating temperature, min. | -40 °C |
| Storage temperature, max. | 85 °C | Storage temperature, min. | -40 °C |
| Operating temperature | -40 °C...60 °C | Storage temperature | -40 °C...85 °C |

Cross-connection data

| | | | |
|------------------|---------|-------------------------------------|----------------------|
| Rated voltage | 250 V | Rated current | 17.5 A |
| Insulation | Yes | Touch-safe protection | Yes |
| Colour | yellow | Number of cross-connected terminals | 19 |
| Number of poles | 19 | Pitch in mm (P) | 6.4 mm |
| Type of mounting | Plugged | Version | can be cut to length |

Rated data UL

| | |
|--------------------|------|
| Rated current (UL) | 10 A |
|--------------------|------|

General data

| | | | |
|---------------------------|----------------------|--------|--------|
| Version | can be cut to length | Colour | yellow |
| UL 94 flammability rating | V-0 | | |

Insulation coordination

| | |
|---------------|-------|
| Rated voltage | 250 V |
|---------------|-------|

Connection data

| | |
|-----------------|--------|
| Pitch in mm (P) | 6.4 mm |
|-----------------|--------|

Classifications

| | | | |
|------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002586 | ETIM 7.0 | EC002586 |
| eClass 9.1 | 27-37-16-92 | eClass 10.0 | 27-37-16-92 |

Approvals

Approvals



ROHS Conform

Data sheet**TERMSERIES**
ZQV 1.5N/R6.4/19 GE**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Technical data****Downloads**

| | |
|--------------------|---|
| Brochure/Catalogue | CAT 4.2 ELECTR 18/19 EN |
| Engineering Data | EPLAN, WSCAD |
| Engineering Data | STEP |
| User Documentation | Beipackzettel / Package Insert - multilingual |


Data sheet

TERMSERIES
ZQV 1.5N/R6.4/19 GE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensional drawing



Data sheet

**TERMSERIES
ZQV 1.5N/R6.4/19 GE**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Cutting and notching tools for cross-connections



- for Weidmüller Z-Series cross-connections
- for cross-connections from WQV 2.5 to WQV 35
- for cross-connection window of the terminal WSI 6

General ordering data

| | | |
|------------|----------------------------|-------------------------------------|
| Type | WAW 1 NEUTRAL | Version |
| Order No. | 9004500000 | Miscellaneous tools |
| GTIN (EAN) | 4008190053925 | |
| Qty. | 1 pc(s). | |
| Type | KT ZQV | Version |
| Order No. | 9002170000 | Cutting tool for one-hand operation |
| GTIN (EAN) | 4032248291670 | |
| Qty. | 1 pc(s). | |

Cutting tools for outside diameters up to 22 mm



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

| | | |
|------------|----------------------------|--|
| Type | KT 14 | Version |
| Order No. | 1157820000 | Cutting tools ,Cutting tool for one-hand operation |
| GTIN (EAN) | 4032248945344 | |
| Qty. | 1 pc(s). | |