



### Main

Range of product	ICT
Device short name	IACts
Product or component type	Remote indication auxiliary
Signal contacts composition	1 NO + 1 NC

### Complementary

[Ie] rated operational current	1 A DC 130 V 2 A AC 50/60 Hz 240 V 0.01 A DC 24 V 0.01 A AC 24 V
Mounting mode	Fixed, on the right of CT
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	1
Height	81 mm
Width	9 mm
Depth	60 mm
Colour	White
Auxiliary connection terminal	Tunnel type terminals 2 cable(s) flexible 2.5 mm <sup>2</sup> Tunnel type terminals 2 cable(s) rigid 1.5 mm <sup>2</sup>
Product compatibility	ICT

### Environment

Standards	EN 60947-5
Tropicalisation	2
Relative humidity	95 % ( 55 °C )
Ambient air temperature for operation	-5...50 °C

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---