



### Main

Range	Acti 9
Product name	Acti 9 iCT
Product or component type	Contactor
Device short name	ICT
Device application	Motor-heating-lighting
Poles description	2P
[Ie] rated operational current	25 A AC-7A 8.5 A AC-7B
Pole contact composition	2 NO
Network type	AC
Control type	Remote control
[Uc] control circuit voltage	230...240 V AC 50 Hz

### Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	250 V AC 50 Hz
Maximum power	1.2 W 250 V AC
[Ui] rated insulation voltage	500 V AC 50 Hz
[Uimp] rated impulse withstand voltage	4 kV
Control signal type	Maintained
Switching frequency	100 switching operations/day
Local signalling	Action indicator
Hold-in power consumption in VA	2.7 VA
Inrush power in VA	9.2 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm

Depth	68.5 mm
Colour	White
Electrical durability	200000 cycles AC 50/60 Hz, AC-7A conforming to IEC/EN 61095 30000 cycles AC 50/60 Hz, AC-7B conforming to IEC/EN 61095 30000 cycles AC 50/60 Hz, AC-7C conforming to IEC/EN 61095 200000 cycles AC 50/60 Hz, AC-1 conforming to EN/IEC 60947-4-1 30000 cycles AC 50/60 Hz, AC-3 conforming to EN/IEC 60947-4-1 30000 cycles AC 50/60 Hz, AC-5A conforming to EN/IEC 60947-4-1 30000 cycles AC 50/60 Hz, AC-5B conforming to EN/IEC 60947-4-1
Connections - terminals	Control circuit : 2 tunnel type terminals 1.5 mm <sup>2</sup> for rigid cable(s) Power circuit : 1 tunnel type terminals 1...4 mm <sup>2</sup> for flexible cable(s) Power circuit : 1 tunnel type terminals 1.5...6 mm <sup>2</sup> for rigid cable(s) Control circuit : 1 tunnel type terminals 1.5...2.5 mm <sup>2</sup> for rigid cable(s) Control circuit : 2 tunnel type terminals 1.5...2.5 mm <sup>2</sup> for flexible cable(s)
Tightening torque	Control circuit : 0.8 N.m Power circuit : 0.8 N.m
Product compatibility	IACTc IACTp IACTs IATEt IACT 24

## Environment

Standards	EN 61095 IEC 1095
Noise level	30 dB
Heat dissipation	0.9 W at 50/60 Hz
IP degree of protection	IP40 (in modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
Pollution degree	2
Tropicalisation	2 2 conforming to IEC 60068-1
Relative humidity	95 % (55 °C)
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...70 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------