



### Main

Range	Acti 9
Product or component type	Shunt trip release
Device short name	IMX
[Uc] control circuit voltage	12 V AC 50/60 Hz 24 V AC 50/60 Hz
9 mm pitches	2

### Complementary

Range compatibility	Acti 9: Acti 9 iC65
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> flexible with cable end cable end
Tightening torque	1 N.m

### Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

**Contractual warranty**

Warranty period	18 months
-----------------	-----------