

PNOZ s9 24VDC 3 n/o 1 n/c t

750109



Technical details

| | |
|--|---|
| Approvals: | CE;cULus Listed;TÜV;KOSHA;CCC |
| Application options: | Instantaneous contact expansion;Delayed contact expansion;Safe delay-on de-energ. timer;Safe delay-on energisation timer;Safe pulsing timer |
| Standards: | EN 60204-1;EN 62061;VDE 0113-1 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal style: | Plug-in |
| Terminal type: | Screw terminal |
| Number of delayed safety contacts: | 3 |
| Safety contact delay type: | Delay-on de-energisation;delay-on energisation;pulsing |
| Number of delayed auxiliary contacts: | 1 |
| Auxiliary contact delay type: | pulsing;delay-on energisation;Delay-on de-energisation |
| Selectable times: | 0.04 s;0.10 s;0.20 s;0.30 s;0.40 s;0.50 s;0.60 s;0.70 s;0.80 s;1.00 s;1.50 s;10.00 s;100.00 s;12.00 s;120.00 s;14.00 s;140.00 s;15.00 s;150.00 s;16.00 s;160.00 s;180.00 s;2.00 s;2.50 s;20.00 s;200.00 s;210.00 s;240.00 s;25.00 s;3.00 s;3.50 s;30.00 s;300.00 s;35.00 s;4.00 s;40.00 s;5.00 s;50.00 s;6.00 s;60.00 s;7.00 s;70.00 s;8.00 s;80.00 s;90.00 s |
| Stop category: | 0/1 |
| Max. current at DC13 I (6 cycles/min): | 5.0 A |
| Max. current at AC15: | 5.0 A |
| Width dimension: | 17.5 mm |
| Height dimension: | 98.0 mm |

| | |
|----------------------|-------------|
| Depth dimension: | 120.0 mm |
| Gross weight: | 185 g |
| Net weight: | 175 g |
| Ambient temperature: | -15 - 55 °C |

Optional accessories



750003

PNOZ s Setscrew terminals 17,5mm



750020

PNOZ s connector (10 pieces)