## Compact enclosure AX Basic enclosure AX, sheet steel – AX 1260.000

Date: Mar 23, 2020

## Compact enclosure AX Basic enclosure AX, sheet steel – AX 1260.000

: 23.03.2020 build on www.rittal.com/uk-en



Product description	n
Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Type rating to UL 508A:	Type 3R/4
Supply includes:	Enclosure with door(s) Gland plate(s) in enclosure base Mounting plate Perforated door strip Lock: 3 mm double-bit
Basic material:	Sheet steel
Product features	
Dimensions:	Width: 600 mm Height: 1200 mm

© Rittal 2020

Depth: 300 mm

Material thickness: Enclosure: 1.5 mm Door: 2 mm Mounting plate: 2.5 mm Width: 545 mm Mounting plate: Height: 1175 mm Number of doors: 1

right, may be

swapped to the left:

Door hinged on the

yes

3-point lock system: yes

Lock version: 3-point lock system

1 Number of locks:

Lock insert: 3 mm double-bit

7 Gland plate, size:

Gland plate, qty.: 1

Packs of: 1 pc(s).

Weight/pack: 50 kg

EAN: 4028177813274

**Customs tariff** number:

94032080

ETIM 7.0: EC000261

ETIM 6.0: EC000261

27180101 eCl@ss 8.0/8.1:

eCl@ss 6.0/6.1: 27180101

**Product description:** AX Compact enclosure, WHD: 600x1200x300 mm, sheet steel, with mounting plate,

single-door, with 3-point lock system

**Approvals** 

UL + C-UL Approvals:

**Declarations:** Declaration of conformity

© Rittal 2020 2

© Rittal 2020

3