## Rittal - The System.

Faster - better - everywhere.

## Plastic enclosures AX without viewing window – AX 1432.000

Date: Mar 2, 2021



ENCLOSURES >> POWER DISTRIBUTION >> CLIMATE CONTROL >> IT INFRASTRUCTURE >> SOFTWARE & SERVICES >>

## Plastic enclosures AX without viewing window – AX 1432.000

created: 02.03.2021 on www.rittal.com/com-en



| Product description                   |  |
|---------------------------------------|--|
| Design:                               | without viewing window   |
| Applications:                         | Ambient temperature range: -30 °C+75 °C The specified temperatures may be limited by the installed equipment   |
| Material:                             | Enclosure and door: Fibreglass-reinforced unsaturated polyester Door: All-round foamed-in PU seal Mounting plate: Sheet steel Fire protection corresponding to UL 94-V0 Halogen free |
| Surface finish:                       | Enclosure and door: Dyed plastic with no after-treatment Mounting plate: Zinc-plated   |
| Colour:                               | Similar to RAL 7035  |
| Protection category IP to IEC 60 529: | IP 66  |
| Protection category NEMA:             | NEMA 4X  |
| Type rating to UL 508A:               | Type 4X  |
| IK Code:                              | IK09   |
| Protection class:                     | II (at 1000 V AC)  |
| Supply includes:                      | Enclosure with hinged door, of all-round solid construction, 3 mm double-bit lock Door hinged on the right, may be swapped to the left   |

© Rittal 2021

Mounting plate

Twin seal on the top and bottom edges of the door as integral rain protection strip

Note: Interior installation screws are required to secure components inside the enclosure

Components such as punched sections with mounting flanges may be attached on a 25

mm pitch pattern using the universal bracket

Basic material: Plastic

**Product description** 

**Dimensions:** Width: 250 mm

Height: 350 mm Depth: 150 mm

Material thickness: Mounting plate: 2.5 mm

Mounting plate: Width: 155 mm

Height: 275 mm

Number of cam locks: 1

Packs of: 1 pc(s).

Weight/pack: 4.8 kg

**EAN**: 4028177006348

Customs tariff number:

94037000

**ETIM 7.0:** EC000261

**ETIM 6.0:** EC000261

eCl@ss 8.0/8.1: 27180101

**eCl@ss 6.0/6.1**: 27180101

**Product description:** AX compact enclosure, plastic, WHD: 250x350x150 mm

**Approvals** 

Approvals: UL + C-UL

Certificates: Negative certificate

Protection category

**Declarations:** Declaration of conformity

© Rittal 2021 2

© Rittal 2021