Rittal – The System.

Faster – better – everywhere.

Plastic enclosures AX without viewing window – AX 1480.000

Date : Mar 26, 2021



ENCLOSURES

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Plastic enclosures AX without viewing window – AX 1480.000

created: 26.03.2021 build on www.rittal.com/uk-en



Product description	
Design:	without viewing window
Applications:	Ambient temperature range: -30 °C+75 °C The specified temperatures may be limited by the installed equipment
Material:	Enclosure and door: Fibreglass-reinforced unsaturated polyester Door: All-round foamed-in PU seal Mounting plate: Sheet steel Fire protection corresponding to UL 94-V0 Halogen free
Surface finish:	Enclosure and door: Dyed plastic with no after-treatment Mounting plate: Zinc-plated
Colour:	Similar to RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Type rating to UL 50E:	Туре 4Х
IK Code:	IK09
Protection class:	II (at 1000 V AC)
Supply includes:	Enclosure with hinged door, of all-round solid construction, 3 mm double-bit lock Door hinged on the right, may be swapped to the left

Mounting plate Twin seal on the top and bottom edges of the door as integral rain protection strip

Note:

Interior installation screws are required to secure components inside the enclosure Components such as punched sections with mounting flanges may be attached on a 25 mm pitch pattern using the universal bracket

Basic material:	Plastic
Product description	
Dimensions:	Width: 800mm Height: 1000mm Depth: 300mm
Material thickness:	Mounting plate: 3 mm
Mounting plate:	Width: 705 mm Height: 925 mm
Number of cam locks:	3
Packs of:	1 pc(s).
Weight/pack:	38.7 kg
EAN:	4028177007086
Customs tariff number:	94037000
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	AX compact enclosure, plastic, WHD: 800x1000x300 mm
Approvals	
Approvals:	UL + C-UL
Certificates:	Negative certificate
Declarations:	Declaration of conformity