

Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling unit
Blue e Total cooling
output 1.00 - 1.50 kW
– SK 3304.600**

Date : Jan 24, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm wall-mounted cooling unit Blue e Total cooling output 1.00 - 1.50 kW – SK 3304.600

created: 24.01.2019 build on www.rittal.com/uk-en



Product description

Material:	Stainless steel
Protection category IP to IEC 60 529:	External circuit IP 34 Internal circuit IP 54
Supply includes:	Nano-coated condenser Integral electric condensate evaporation Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts
Note on Model No.:	Extended delivery times.

Product features

Variant:	wall-mounted
Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 1.1 kW L 35 L 35 at 60 Hz: 1.25 kW L 35 L 50 at 50 Hz: 0.91 kW L 35 L 50 at 60 Hz: 0.9 kW
Air throughput (unimpeded air flow):	External circuit: 805 m ³ /h Internal circuit: 600 m ³ /h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 400 mm Height: 950 mm

Depth: 260 mm

Temperature control:	e-Comfort controller (factory setting +35 °C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 325 g Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO ₂ e): 0.46 t
Power consumption P_{sub-el-subcl}:	L 35 L 35 at 50 Hz: 0.6 kW L 35 L 35 at 60 Hz: 0.68 kW L 35 L 50 at 50 Hz: 0.71 kW L 35 L 50 at 60 Hz: 0.81 kW
Rated current (max.):	At 50 Hz: 3.9 A At 60 Hz: 4.3 A
Start-up current max.:	At 50 Hz: 12 A At 60 Hz: 14 A
Miniature circuit-breaker/fuse:	10 A
Permissible operating pressure (p. max.):	28 bar
Packs of:	1 pc(s).
Weight/pack:	39 kg
EAN:	4028177379695
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Product description:	SK cooling unit Blue e, wall-mounted, 1.1 kW, 230 V, 1~, 50/60 Hz, Stainless steel, WHD: 400 x 950 x 260 mm

Approvals

Approvals:	CSA TÜV-tested safety UL + C-UL - FTTA UR + C-UR
-------------------	---

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation
----------------------	---