Rittal - The System.


Faster – better – everywhere.

Conductor connection clamp – SV 3456.500



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Conductor connection clamp — SV 3456.500 created: 26.11.2019 build on www.rittal.com/uk-en



Product description	
Description:	For connecting round conductors and laminated copper bars.
Material:	Sheet steel
Surface finish:	Zinc-plated, passivated
Note:	Wire end ferrules should be used with fine wire conductors
Product features	
To fit busbars:	Cross-section (thickness): 10 mm
Clamping area for laminated copper bars:	Width: 8 mm Height: 8 mm
Connection for round conductor cross-sections:	2,5 mm² - 16 mm²
Packs of:	15 pc(s).
Weight/pack:	0.44 kg
Copper weight (kg per piece):	0
EAN:	4028177042742
Customs tariff number:	85369010

© Rittal 2019

ETIM 7.0:	EC000001
ETIM 6.0:	EC000001
e CI@ss 8.0/8.1:	27141146
e Cl@ss 6.0/6.1:	27141146
Product description:	SV Conductor connection clamp, 2,5-16 mm², clamping area WH: 8x8 mm, for bar thickness 10 mm
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2019 2