

Rittal – The System.

Faster – better – everywhere.

Laminated copper bars – SV 3573.005

Date : Jan 24, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Laminated copper bars – SV 3573.005

created: 24.01.2019 build on www.rittal.com/uk-en



Product description

Material: Cu lamina High-purity electrolyte copper F20
Insulation: High-strength vinyl compound, expansion 370%, dielectric strength: 20 kV/mm
Fire protection corresponding to UL 94-V0

Note: May be cut individually to required length

Product features

Dimensions: Length: 2000 mm

Version – laminated flat copper: Number of lamina: 5
Membrane width: 32 mm
Membrane thickness: 1 mm

Operating temperature: -30°C...+105°C

Rated current for temperature increase by: 70 K: 770 A
50 K: 645 A
30 K: 485 A

Packs of: 1 pc(s).

Weight/pack: 3.4 kg

EAN: 4028177666795

Customs tariff number: 74071000

ETIM 6.0:	EC001522
ETIM 5.0:	EC001522
eCl@ss 8.0/8.1:	27370303
eCl@ss 7.0/7.1:	27370303
eCl@ss 6.0/6.1:	27370303
eCl@ss 5.1/5.1.4:	27370302
Product description:	SV Laminated copper bar, WH: 32x5 mm, L: 2000 mm

Approvals

Approvals:	C-UR UR UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity