

Rittal – The System.

Faster – better – everywhere.

Threaded blocks – TS 4162.000

Date : Nov 26, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Threaded blocks – TS 4162.000

created: 26.11.2019 build on www.rittal.com/uk-en



Product description

Description: With snap-off insertion aid, die-cast zinc.

Product features

Installation options:

- On the horizontal and vertical VX enclosure section
- Punched section with mounting flange, 23 x 64 mm
- Punched section with mounting flange, 23 x 89 mm, stainless steel
- On enclosures and rails with rectangular system punching 12.5 x 10.5 mm.
- Vertical TS, SE enclosure section via adaptor rails for PS compatibility
- TS horizontal, direct
- On the horizontal SE enclosure section, bottom, directly
- On the horizontal SE enclosure section, (only top in the depth), directly
- Punched rails 23 x 23 mm for TS, SE
- Punched section without mounting flange, 23 x 73 mm, for TS, SE
- Punched section without mounting flange, 45 x 88 mm, for TS, SE
- Punched section with mounting flange, 23 x 73 mm, for TS, SE

Thread: Type: M6

Packs of: 50 pc(s).

Weight/pack: 0.5 kg

Copper weight (kg per piece): 0

EAN: 4028177092945

Customs tariff number: 79070000

ETIM 7.0: EC002358

ETIM 6.0:	EC002358
eCl@ss 8.0/8.1:	23110815
eCl@ss 6.0/6.1:	27189234
Product description:	TS Threaded block, for thread M6
