

# Rittal – The System.

Faster – better – everywhere.

## ► Wall-mounted enclosures AX IT with 482.6 mm (19") mounting angles, depth-variable – AX IT 7645.350

Date : Jan 10, 2022

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted enclosures AX IT with 482.6 mm (19") mounting angles, depth-variable – AX IT 7645.350

created: 10.01.2022 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

<b>Description:</b>	IT wall-mounted enclosure based on AX, with high protection category, for use in industrial environments.
<b>Benefits:</b>	Fully pre-assembled IT enclosure for immediate accommodation of 482.6 mm (19") IT components, with depth-variable mounting angles Welded enclosure construction with all-round solid body ensures maximum protection for installed components, up to IP 66 Door hinged on the right, may be swapped to the left Maximum usable interior volume with an extremely compact design Individual interior configuration Maximum cut-out in the enclosure base with optimised gland plates increases the space for cable routing by up to 33% Convenient cable entry from below via a gland plate with integral brush strip
<b>Applications:</b>	IT enclosure for use in industrial environments Secure, protected integration of IT directly into your production plant processes
<b>Installation options:</b>	Pre-configured mounting bracket including C rail for cable clamping Mounting bracket to accommodate a central earth rail Mounting bracket for mounting a 482.6 mm (19") socket strip
<b>Material:</b>	Sheet steel
<b>Surface finish:</b>	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Interior installation: Zinc-plated
<b>General colour:</b>	RAL 7035
<b>Colour:</b>	RAL 7035

<b>Protection category IP to IEC 60 529:</b>	IP 10 (up to IP 66 on request) Up to IP 66 (depending on the selected gland pate)
--	--

<b>Supply includes:</b>	Pre-assembled IT enclosure with hinged door, of all-round solid construction Cam lock with 3 mm double-bit insert Gland plate with brush strip 482.6 mm (19") mounting angle, front, mounted onto four interior installation rails with depth adjustment in 25 mm pitch pattern Mounting bracket C rail, fastened to the rear panel
-------------------------	--

<b>Note:</b>	Variant with UL approval available on request
--------------	---

<b>Basic material:</b>	Sheet steel
------------------------	-------------

## Product description

<b>Dimensions:</b>	Width: 600 mm Height: 760 mm Depth: 350 mm
--------------------	--

<b>Installation height for components:</b>	15 U
--	------

<b>Installation depth:</b>	278 mm
----------------------------	--------

<b>Door hinge:</b>	right, may be swapped to the left
--------------------	-----------------------------------

<b>Number of cam locks:</b>	2
-----------------------------	---

<b>Lock version:</b>	Cam lock with 3 mm double-bit lock insert
----------------------	---

<b>Number of locks:</b>	2
-------------------------	---

<b>Gland plate, size:</b>	7
---------------------------	---

<b>Gland plate, qty.:</b>	1
---------------------------	---

<b>Packs of:</b>	1 pc(s).
------------------	----------

<b>Weight/pack:</b>	29.64 kg
---------------------	----------

<b>EAN:</b>	4028177942417
-------------	---------------

<b>Customs tariff number:</b>	94032080
-----------------------------------	----------

<b>ETIM 7.0:</b>	EC002500
------------------	----------

<b>ETIM 6.0:</b>	EC002500
------------------	----------

eCl@ss 8.0/8.1: 27180208

---

eCl@ss 6.0/6.1: 27180208

---

**Product description:** AX IT wall-mounted IT distributor, 15 U, without mounting plate, with 482.6 mm (19") mounting angles, WHD: 600x760x350 mm (AX 1376), Pre-assembled IT enclosure with:, with hinged door, of all-round solid construction

---

## Approvals

---

**Certificates:** NA

---

**Declarations:** Declaration of conformity

---