

Rittal – The System.

Faster – better – everywhere.

Busbar supports flat copper busbars – SV 9340.004

Date : Jan 11, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Busbar supports flat copper busbars – SV 9340.004

created: 11.01.2019 build on www.rittal.com/uk-en



Product description

Material:	Polyamide (PA 6.6) Fire protection corresponding to UL 94-V0
Colour:	RAL 7035
Note:	If 12 x 5/10 mm busbars are used, the spacer 9340.090 is additionally required The use of a base tray is required for UL applications UL approval only applies in conjunction with AC application

Product features

To fit busbars:	With dimensions (mm): 12 x 5 - 30 x 10
Number of poles:	4-pole
Centre-to-centre spacing of busbars:	60 mm
Internal attachment:	yes
Packs of:	4 pc(s).
Weight/pack:	0.92 kg
EAN:	4028177536715
Customs tariff number:	85469010
ETIM 6.0:	EC001166

ETIM 5.0:	EC001166
eCl@ss 8.0/8.1:	27400607
eCl@ss 7.0/7.1:	27400607
eCl@ss 6.0/6.1:	27400607
eCl@ss 5.1/5.1.4:	27370302
Product description:	SV Busbar support, 4-pole, 60 mm bar centre distance, for busbar WH: 12x5-30x10 mm, UL design
Approvals	
Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity