

Rittal – The System.

Faster – better – everywhere.

OM adaptors with connection cables – SV 9340.340

Date : Jan 14, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with connection cables – SV 9340.340

created: 14.01.2019 build on www.rittal.com/uk-en



Product description

Material:	Polyamide (PA 6.6) Fire protection corresponding to UL 94-V0
Colour:	Chassis: RAL 7035
Note:	The technical data may vary for UL applications

Product features

To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
------------------------	---

Number of poles:	3-pole
-------------------------	--------

For bar systems with centre-to-centre spacing:	60 mm
---	-------

Dimensions:	Width: 45 mm Height: 208 mm
--------------------	--------------------------------

Connection cable:	Cross-section: AWG 12 Length: 130 mm
--------------------------	---

Support frame:	Width: 45 mm Height: 170 mm
-----------------------	--------------------------------

Rated current (max.):	25 A
------------------------------	------

Number of support	1
--------------------------	---

rails:	
Height of support rails:	10 mm
Support rail type:	TS 45C
Packs of:	1 pc(s).
Weight/pack:	0.28 kg
EAN:	4028177502512
Customs tariff number:	85369095
ETIM 6.0:	EC001531
ETIM 5.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 7.0/7.1:	27370304
eCl@ss 6.0/6.1:	27370304
eCl@ss 5.1/5.1.4:	27370302
Product description:	SV OM adaptor, 25 A, 690 V, 3-pole, connection cable AWG 12, WH: 45x208 mm, support frame, support rail TS 45C

Approvals

Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity