Rittal – The System.

Faster – better – everywhere.

OM adaptors with connection cables – SV 9340.470

Date : Oct 29, 2019



ENCLOSURES

X IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

OM adaptors with connection cables – SV 9340.470 created: 29.10.2019 build on www.rittal.com/uk-en



Product description	
Material:	Polyamide Fire protection corresponding to UL 94-V0
Colour:	Chassis: RAL 7035
Note:	The technical data may vary for UL applications
Product features	
To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 55 mm Height: 208 mm
Rated current max.:	32 A
Rated operating voltage:	690 V, 3~
Connection cable:	Cross-section: AWG 10 Length: 130 mm
Support frame:	Width: 55 mm Height: 170 mm

1

Number of support rails:	2
Height of support rails:	10 mm
Support rail type:	TS 55D TS 55D-V
Packs of:	1 pc(s).
Weight/pack:	0.36 kg
Copper weight (kg per piece):	0.07
EAN:	4028177555457
Customs tariff number:	85369095
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV OM adaptor, 32 A, 690 V, 3-pole, connection cable AWG 10, WH: 55x208 mm, support frame, support rail TS 55D, TS55D-V
Approvals	
Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity