

# Rittal – The System.

Faster – better – everywhere.

## **OM adaptors with spring terminals – SV 9340.510**

Date : Nov 29, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# OM adaptors with spring terminals – SV 9340.510

created: 29.11.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Material:** Polyamide  
Fire protection corresponding to UL 94-V0

**Colour:** Chassis: RAL 7035

## Product features

**To fit busbars:** with cross-section height: 5 mm  
with cross-section height: 10 mm

**Number of poles:** 3-pole

**For bar systems with centre-to-centre spacing:** 60 mm

**Dimensions:** Width: 45 mm  
Height: 208 mm

**Rated current max.:** 32 A

**Rated operating voltage:** 690 V, 3~

**Connection for round conductor cross-sections:** 1,5 mm<sup>2</sup> - 6 mm<sup>2</sup>

**Number of support rails:** 1

**Height of support rails:** 10 mm

<b>Support rail type:</b>	TS 45C
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	0.24 kg
<b>Copper weight (kg per piece):</b>	0.03
<b>EAN:</b>	4028177502611
<b>Customs tariff number:</b>	85369095
<b>ETIM 7.0:</b>	EC001531
<b>ETIM 6.0:</b>	EC001531
<b>eCl@ss 8.0/8.1:</b>	27370304
<b>eCl@ss 6.0/6.1:</b>	27370304
<b>Product description:</b>	SV OM adaptor, 32 A, 690 V, 3-pole, tension spring clamp 1,5-6 mm <sup>2</sup> , WH: 45x208 mm, support rail TS 45C

## Approvals

**Approvals:** ABS  
 DNV-GL  
 Lloyds Register of Shipping

**Certificates:** EAC

**Declarations:** Declaration of conformity