

Rittal – The System.

Faster – better – everywhere.

OM adaptors with tension spring clamp – SV 9340.530

Date : Jan 14, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with tension spring clamp – SV 9340.530

created: 14.01.2019 build on www.rittal.com/uk-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Colour: Chassis: RAL 7035

Product features

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 45 mm
Height: 208 mm

Connection for round conductor cross-sections: 1,5 mm² - 6 mm²

Support frame: Width: 45 mm
Height: 170 mm

Rated current (max.): 32 A

Number of support rails: 1

Height of support 10 mm

rails:

Support rail type:	TS 45C
Packs of:	1 pc(s).
Weight/pack:	0.26 kg
EAN:	4028177502628
Customs tariff number:	85369095
ETIM 6.0:	EC001531
ETIM 5.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 7.0/7.1:	27370304
eCl@ss 6.0/6.1:	27370304
eCl@ss 5.1/5.1.4:	27370302
Product description:	SV OM adaptor, 32 A, 690 V, 3-pole, tension spring clamp 1,5-6 mm ² , WH: 45x208 mm, support frame, support rail TS 45C

Approvals

Approvals:	ABS DNV-GL Lloyds Register of Shipping
Certificates:	EAC
Declarations:	Declaration of conformity