

Rittal – The System.

Faster – better – everywhere.

OM adaptors with spring terminals – SV 9340.660

Date : Nov 29, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with spring terminals – SV 9340.660

created: 29.11.2019 build on www.rittal.com/uk-en



Product description

Material: Polyamide
Fire protection corresponding to UL 94-V0

Colour: Chassis: RAL 7035

Product features

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 55 mm
Height: 208 mm

Rated current max.: 32 A

Rated operating voltage: 690 V, 3~

Connection for round conductor cross-sections: 1,5 mm² - 6 mm²

Support frame: Width: 55 mm
Height: 170 mm

Number of support 1

rails:	
Height of support rails:	10 mm
Support rail type:	TS 55D
Packs of:	1 pc(s).
Weight/pack:	0.28 kg
Copper weight (kg per piece):	0.03
EAN:	4028177502680
Customs tariff number:	85369095
ETIM 7.0:	EC001531
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV OM adaptor, 32 A, 690 V, 3-pole, tension spring clamp 1,5-6 mm ² , WH: 55x208 mm, support frame, support rail TS 45D
Approvals	
Approvals:	ABS DNV-GL Lloyds Register of Shipping
Certificates:	EAC
Declarations:	Declaration of conformity