

Rittal – The System.

Faster – better – everywhere.

NH fuse-switch- disconnectors, size 00 to 3 – SV 9343.100

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch-disconnectors, size 00 to 3 – SV 9343.100

created: 16.01.2019 build on www.rittal.com/uk-en



Product description

Material:	Polyamide (PA 6) Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated
Colour:	Chassis: RAL 7035 Cover: RAL 7035/7001
Basis of test:	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
Note:	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".

Product features

Design:	Size: 1
To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 184 mm Height: 298 mm

Type of electrical connection:	Box terminal
Clamping area for laminated copper bars:	Width: 20 mm Height: 3 mm Height: 14 mm
Connection for round conductor cross-sections:	35 mm ² - 150 mm ² Note: Connection of sector-shaped conductors 50 – 150 mm ² .
Rated operating current max.:	250 A
Cable outlet:	Top/bottom
Weight/pack:	2.34 kg
ETIM 5.0:	EC001040
eCl@ss 6.0/6.1:	27371401
Product description:	SV NH fuse-switch disconnecter, size 1, 250 A, 690 V, 3-pole, box terminal
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity