

# Rittal – The System.

Faster – better – everywhere.

## **NH fuse-switch- disconnectors, size 00 to 3 – SV 9343.110**

Date : Nov 18, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# NH fuse-switch-disconnectors, size 00 to 3 – SV 9343.110

created: 18.11.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

<b>Material:</b>	Polyamide Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated
<b>Colour:</b>	Chassis: RAL 7035 Cover: RAL 7035/7001
<b>Basis of test:</b>	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
<b>Note:</b>	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".

## Product features

<b>Design:</b>	Size: 1
<b>To fit busbars:</b>	with cross-section height: 5 mm with cross-section height: 10 mm
<b>Number of poles:</b>	3-pole
<b>For bar systems with centre-to-centre spacing:</b>	60 mm
<b>Dimensions:</b>	Width: 184 mm Height: 298 mm

<b>Type of electrical connection:</b>	Screw M10
<b>Rated operating voltage:</b>	690 V, 3~
<b>Clamping area for laminated copper bars:</b>	Width: 32 mm Height: 10 mm
<b>Connection for round conductor cross-sections:</b>	10 mm <sup>2</sup> - 150 mm <sup>2</sup>
<b>Rated operating current max.:</b>	250 A
<b>Cable outlet:</b>	Top/bottom
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	2.26 kg
<b>Copper weight (kg per piece):</b>	0.44
<b>EAN:</b>	4028177540330
<b>Customs tariff number:</b>	85369095
<b>ETIM 7.0:</b>	EC001040
<b>ETIM 6.0:</b>	EC001040
<b>eCl@ss 8.0/8.1:</b>	27371401
<b>eCl@ss 6.0/6.1:</b>	27371401
<b>Product description:</b>	SV NH fuse-switch disconnecter, size 1, 250 A, 690 V , 3-pole, screw M10

## Approvals

<b>Approvals:</b>	C-UR CCC UR
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity