

Rittal – The System.

Faster – better – everywhere.

NH fuse-switch- disconnectors, size 00 to 3 – SV 9343.310

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch-disconnectors, size 00 to 3 – SV 9343.310

created: 16.01.2019 build on www.rittal.com/uk-en



Product description

Material: Polyamide (PA 6)
Fire protection corresponding to UL 94-V0
Contact tracks: Electrolytic copper, silver-plated

Colour: Chassis: RAL 7035
Cover: RAL 7035/7001

Basis of test: IEC/DIN EN 60 947-3
DIN EN 60 269-2 (fuse inserts)

Note: The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".

Product features

Design: Size: 3

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 250 mm
Height: 298 mm

Type of electrical connection:	Screw M10
Clamping area for laminated copper bars:	Width: 50 mm Height: 10 mm
Connection for round conductor cross-sections:	10 mm ² - 300 mm ²
Rated operating current max.:	630 A
Cable outlet:	Top/bottom
Weight/pack:	4.22 kg
ETIM 5.0:	EC001040
eCl@ss 6.0/6.1:	27371401
Product description:	SV NH fuse-switch disconnecter, size 3, 630 A, 690 V, 3-pole, screw M10
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity