

# Rittal – The System.

Faster – better – everywhere.

## ▶ NH fuse-switch- disconnectors, size 00 to 3 – SV 9344.110

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# NH fuse-switch-disconnectors, size 00 to 3 – SV 9344.110

created: 16.01.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

<b>Material:</b>	Polyamide (PA 6) Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated
<b>Colour:</b>	Chassis: RAL 7035 Cover: RAL 7035/7001
<b>Basis of test:</b>	IEC/DIN EN 60 947-3 DIN EN 60 269-2 (fuse inserts)
<b>Note:</b>	The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".

## Product features

<b>Design:</b>	Size: 1
<b>Number of poles:</b>	3-pole
<b>For mounting plate assembly:</b>	yes
<b>Dimensions:</b>	Width: 184 mm Height: 298 mm
<b>Type of electrical connection:</b>	Screw M10
<b>Clamping area for laminated copper</b>	Width: 32 mm Height: 10 mm

bars:

<b>Connection for round conductor cross-sections:</b>	10 mm <sup>2</sup> - 150 mm <sup>2</sup>
<b>Rated operating current max.:</b>	250 A
<b>Cable outlet:</b>	Top/bottom
<b>Weight/pack:</b>	2.14 kg
<b>ETIM 5.0:</b>	EC001040
<b>eCl@ss 6.0/6.1:</b>	27371401
<b>Product description:</b>	SV NH fuse-switch disconnecter, size 1, 250 A, 690 V, 3-pole, screw M10, for mounting plate assembly

## Approvals

<b>Approvals:</b>	C-UR UR
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity