

Rittal – The System.

Faster – better – everywhere.

NH slimline fuse- switch disconnectors – SV 9346.010

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH slimline fuse-switch disconnectors – SV 9346.010

created: 16.01.2019 build on www.rittal.com/uk-en



Product description

Material: Fibreglass-reinforced polyamide
Fire protection corresponding to UL 94-V0
Contact tracks: Silver-plated hard copper

Colour: Chassis: RAL 7035
Cover: RAL 7001
Handle: RAL 7016

Basis of test: IEC/DIN EN 60 947-3
DIN EN 60 269-2 (fuse inserts)

Supply includes: 3 mounting hooks

Product features

Design: Size: 00

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 50 mm
Height: 400 mm

Type of electrical connection: Screw M8

Connection for round conductor cross-sections:	2,5 mm ² - 95 mm ²
Rated operating current max.:	160 A
Cable outlet:	Top/bottom
Weight/pack:	1.26 kg
ETIM 5.0:	EC001046
eCl@ss 6.0/6.1:	27371402
Product description:	SV NH slimline fuse-switch disconnecter, size 00, 160 A, 690 V, 3-pole, screw M8, 60 mm
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity