

# Rittal – The System.

Faster – better – everywhere.

## Mini-PLS busbar connection adaptor – SV 9612.000

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Mini-PLS busbar connection adaptor – SV 9612.000

created: 16.01.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Material:** Polyamide (PA 6.6)  
Fire protection corresponding to UL 94-V0

**Colour:** RAL 7035  
Chassis: RAL 9011

## Product features

**Number of poles:** 3-pole

**Dimensions:** Width: 115 mm  
Height: 182 mm

**Clamping area for laminated copper bars:** Width: 17 mm  
Height: 15 mm

**Connection for round conductor cross-sections:** 10 mm<sup>2</sup> - 120 mm<sup>2</sup>  
Note: Wire end ferrules should be used with fine wire conductors.

**Rated current (max.):** 250 A

**Cable outlet:** Top/bottom

**Weight/pack:** 1.08 kg

**ETIM 5.0:** EC001531

**eCl@ss 6.0/6.1:** 27400613

**Product description:** SV Mini-PLS busbar connection adaptor, 250 A, 690 V, 3-pole, round conductor connection 10-120 mm<sup>2</sup>, clamping area WH: 17x15 mm

## Approvals

**Approvals:** C-UR  
UR

**Certificates:** EAC

**Declarations:** Declaration of conformity