

Rittal – The System.

Faster – better – everywhere.

Mini-PLS component adaptor – SV 9614.100

Date : Oct 29, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Mini-PLS component adaptor – SV 9614.100

created: 29.10.2019 build on www.rittal.com/uk-en



Product description

Material: Polyamide
Fire protection corresponding to UL 94-V0

Product features

Number of poles: 3-pole

Dimensions: Width: 45 mm
Height: 160 mm

Rated current max.: 25 A

Rated operating voltage: 690 V, 3~

Connection cable: Cross-section: AWG 12

Number of support rails: 1

Height of support rails: 7.5 mm

To fit manufacturer (model): ABB (MS116)
Eaton (PKZM0 bis 25 A, PKZM01 bis 25 A, PKE12, PKE32 bis 25 A)
Schneider Electric (GV2-P bis 25 A, GV2-RT, GV2-LE10, GV3 bis 25 A)
Siemens (3RV10 21, 3RV20 21 bis 25 A, 3RV10 11, 3RV20 11)

Packs of: 1 pc(s).

Weight/pack: 0.3 kg

Copper weight (kg per piece):	0.04
EAN:	4028177192546
Customs tariff number:	85369095
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV Mini-PLS component adaptor, 25 A, 690 V, 3-pole, connection cable AWG 12, WH: 45x160 mm, support rail H: 7,5 mm
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity