

Rittal – The System.

Faster – better – everywhere.

▶ PE/PEN combination angle E-Cu for PE/PEN combinations – SV 9661.230

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



PE/PEN combination angle E-Cu for PE/PEN combinations – SV 9661.230

created: 16.01.2019 build on www.rittal.com/uk-en



Product description

Description:	The PE/PEN combination, comprising busbars, combination angles and baying brackets, supports type-tested configurations as per IEC 61 439-1.
Benefits:	Thanks to the pre-assembled combination angles, baying brackets and busbars customised to match the enclosure width, assembly is time-saving with cost reduction
Applications:	Form 2-4 Other
Material:	E-Cu
Supply includes:	Assembly parts

Product features

To fit busbars:	Busbar type: Busbar E-Cu with integral punchings with cross-section width: 30 mm with cross-section height: 10 mm
Cross-section:	Cross-section per bracket (width): 30 mm Cross-section per bracket (thickness): 10 mm
Tested short-circuit resistance:	lcw 30 kA, 1 sec.
Weight/pack:	2.18 kg
ETIM 5.0:	EC000329

eCl@ss 8.0/8.1: 27400605

eCl@ss 6.0/6.1: 27400605

Product description: SV PE/PEN combination angle E-Cu, WH: 30x10 mm

Approvals

Declarations: Declaration of conformity
