

Connection Systems

Safety Wired Distribution Box, DC Micro Style

Dual-Channel N.C., No Enunciation





Specifications

Housing Material	Red PBT
Connector Insert Material	PBT
Connector Shell Material	Nickel-plated brass
Contact Material	Gold-plated palladium/nickel
Cable O.D.	9.8 mm (0.39 in)
Cable Type	Oil-resistant yellow PVC jacket, 22 AWG conductors
Enclosure Type Rating	IP 67, NEMA 6P
Operating Temperature—C (F)	-20...105° (-13...221°)

Features

- Prewired for dual-channel N.C. safety
- 4 or 8 safety wired 4-pin DC micro connectors
- 4-pin male DC micro pigtail main connection
- For use in category 2 or 3 systems per EN 954-1


Product Selection

Face View of Female	No. of Ports	Illuminated	Rating	Face View of Male (1)	Cable Length	Cat. No.
	4	No LED	10...30V DC		0.2 m (8 in)	898D-44LT-DM4
	8					898D-48LT-DM4
Shorting plug for unused ports						898D-41LU-DM
Patchcord, straight to straight DC Micro						889D-F4ACDM-*

* Length in meters (1, 2, 3, 5, 10 standard).

Approximate Dimensions—mm (inches)

Dimensions are not intended to be used for installation purposes.



Wiring Diagrams

